



## 1 Gang Cast Aluminum Boxes

- Electrostatically painted with a baked, weather-resistant powder finish for exceptional durability.
- Accept single gang weatherproof covers and standard FS (Four Screw) covers.
- Mounting lugs provide strength and durability on any mounting surface.
- Raised knockout studs on back of box provide alternative means for wall mounting. Strike desired studs with sharp hammer blow for clean mounting holes.
- Easy access ground screw hole located inside back wall of box.
- Threaded outlets for conduit and connectors.
- Two closure plugs and mounting lugs furnished.

### TESTING & CODE COMPLIANCE:

UL514A (file no. E103697) and cUL (file no. E103697) Listed. Meets all CSA requirements C22.2 no.18-92 (file no. LR87187).

### ORDERING INFORMATION:

Catalog No.	End Opening	Back Opening	Description	Weight/ea	Packed/VPE	EDP-No
1113-SP	1-1	1	3 Hole 0.50"	272g	10	100046
1114-SP	2-1	1	4 Hole 0.50"	316g	10	100048
1115-SP	2-2	1	5 Hole 0.50"	262g	10	114464
1116-SP	1-1	1	3 Hole 0.75"	246g	10	114467
1117-SP	2-1	1	4 Hole 0.75"	305g	10	112456
1118-SP	2-2	1	5 Hole 0.75"	349g	10	112457