



Watertight Safety-Shroud Twist-Lock(R) System, UL Listed, CSA Certified,  
Type 4, 4X and Type 12, all Devices are Grounded (\*) Also Suitable for 208V

Receptacle	Male Plug	Connector	Male Inlet	AC HP Rating			Poles	NEMA
2310 SW	2311 SW	2313 SW	2315 SW	1HP	20A	125V	2P 3W	L5-20
2320 SW	2321 SW	2323 SW	2325 SW	2HP	20A	250V (*)	2P 3W	L6-20
2330 SW	2331 SW	2333 SW	2335 SW	2HP	20A	277V AC	2P 3W	L7-20
2410 SW	2411 SW	2413 SW	2415 SW	2HP	20A	125/250V AC	3P 4W	L14-20
2420 SW	2421 SW	2423 SW	2425 SW	3HP	20A	3Ø250V AC	3P 4W	L15-20
2430 SW	2431 SW	2433 SW	2435 SW	5HP	20A	3Ø480V AC	3P 4W	L16-20
2510 SW	2511 SW	2513 SW	2515 SW	2HP	20A	3ØY120/208V AC	4P 5W	L21-20
2610 SW	2611 SW	2613 SW	2615 SW	2HP	30A	125V	2P 3W	L5-30
2620 SW	2621 SW	2623 SW	2625 SW	2HP	30A	250V (*)	2P 3W	L6-30
2710 SW	2711 SW	2713 SW	2715 SW	2HP	30A	125/250V AC	3P 4W	L14-30
2720 SW	2721 SW	2723 SW	2725 SW	3HP	30A	3Ø250V AC	3P 4W	L15-30
2730 SW	2731 SW	2733 SW	2735 SW	10HP	30A	3Ø480V AC	3P 4W	L16-30
2740 SW	2741 SW	2743 SW	2745 SW	--	30A	3Ø600V	3P 4W	L17-30
2810 SW	2811 SW	2813 SW	2815 SW	3HP	30A	3ØY120/208V AC	4P 5W	L21-30