

**Vitalite®
121S****Fireball®
FB2PST**

E94581 C22.2

**Commander®
371L****Starfire®
131DST****DOUBLE FLASH STROBE WARNING LIGHT**

Starfire® Convenient size and intense double flash of light makes this model popular for mounting on cranes & other moving devices, marking dangerous areas, and process control. Features solid-state electronics, impact-resistant polycarbonate fresnel dome, anodized aluminum base which resists rust and corrosion. Produces a double-flash of light 75-85 times per minute. 1200 effective candlepower, peak candlepower 1,000,000*. Designed for 1/2" dia. pipe mount. Amber, Blue, Clear, Green or Red color. 120+240VAC 50/60Hz & 12-24VDC. Magnetic mount optional. UL-Listed & CSA-Approved for indoor/outdoor use; CE Approved; Rated for NEMA Type 3R Applications (IP54).

ECONOMICAL REVOLVING WARNING LIGHT

Vitalite® Compact revolving light for areas where hazardous or dangerous conditions are present & where a constant revolving beam of light is desirable. Single screw dome retainer makes re-lamping easier. 60 flashes per minute. 40w lamp. Designed for 1/2" dia. pipe mount. Amber, Blue, Clear, Green, Magenta or Red color. 120VAC, 60Hz. UL-Listed & CSA-Approved for indoor use; Rated for NEMA Type 3R Applications (IP41).

HEAVY DUTY REVOLVING WARNING LIGHT

Commander® Powerful 100 watt rotating sealed beam lamp in heavy-duty die cast housing. 24 fins dissipate heat for extended life. Approximately 60 flashes per minute producing a revolving beam of light with 20,000 candlepower. Pivotal lamp allows for beam adjustment through 90° Hammetone gray finish base with stainless steel dome retaining ring. Designed for 1" pipe or flat surface mount. Amber, Blue, Clear, Green or Red color. 120VAC 50/60Hz Model is UL-Listed & CSA-Approved for indoor/outdoor use; 125VDC available; Rated for NEMA 4X Applications (IP56).

COMPACT STROBE WARNING LIGHT

Fireball® Effectively brings attention to industrial hazards, and production processes. Features Xenon flash tube, solid-state circuitry, polycarbonate fresnel dome, zinc die cast base painted with a corrosion resistant polyurethane. Produces a brilliant flash 80 times per minute. 300 effective candlepower, peak candlepower 1,000,000*. Designed for 1/2" dia. pipe mount. Amber, Blue, Clear, Green or Red color. 120+240VAC 50/60Hz & 12-24VDC Magnetic or pipe mount. UL-Listed and CSA-Approved for indoor/outdoor use; CE Approved; Rated for NEMA Type 3R Applications (IP45).

(*) Effective candlepower is intensity which would appear to observer if light were burning steadily. Peak candlepower is max. light intensity generate by flashing light during light pulse.

Catalog Number	Color	Voltage	Operating	Overall Dimension	Weight
121S-120A	Amber	120V AC 60 Hz	0.33 Amps	H=165mm Ø=129mm	800g
121S-120R	Red	120V AC 60 Hz	0.33 Amps	H=165mm Ø=129mm	800g
371L-120A	Amber	120V AC 50/60 Hz	0.80 Amps	H=289mm Ø=232mm	4500g
371L-120R	Red	120V AC 50/60 Hz	0.80 Amps	H=289mm Ø=232mm	4500g
FB2PST-120A	Amber	120V AC 50/60 Hz	0.32 Amps	H=126mm Ø=100mm	900g
FB2PST-120R	Red	120V AC 50/60 Hz	0.32 Amps	H=126mm Ø=100mm	900g
131DST-120A	Amber	120V AC 50/60 Hz	0.60 Amps	H=216mm Ø=145mm	1000g
131DST-120R	Red	120V AC 50/60 Hz	0.60 Amps	H=216mm Ø=145mm	1000g