



826/827/828 - Series Permanent/Blinking/Flashing Beacon

- Simple mounting
- Removal of the dome only possible with tools
- Modern design
- High protection rating IP 65 – suitable for indoor and outdoor use

Europe – Permanent/Blinking/Flashing Beacon – Technical Specifications:



Dimensions (Diameter x Height): 100 mm x 138.5 mm
Housing: ABS/PC
Dome: Polycarbonate, transparent
Fixing: Base mounting, bracket mounting, tube mounting
 (Base 975.840.90 must be ordered twice for base mounting – once as socket for beacon and once as base)
Socket: B 15d, B 15s
Operating Temperature: + 50 °C to - 20 °C



Bracket (accessory)



Tube with Base (accessory)

Catalog No. / Katalog-Nr.	Description / Beschreibung	Weight/ea	VPE/Pack	U/M	EDP-No.
826 – Series Permanent Light					
826.100.00	Permanent Light (B 15d), 12-240 V, Red Dome	200g	10	ea	
826.200.00	Permanent Light (B 15d), 12-240 V, Green Dome	200g	10	ea	
826.300.00	Permanent Light (B 15d), 12-240 V, Yellow Dome	200g	10	ea	
826.400.00	Permanent Light (B 15d), 12-240 V, Clear Dome	200g	10	ea	
826.500.00	Permanent Light (B 15d), 12-240 V, Blue Dome	200g	10	ea	
826.120.00	Permanent Light (B 15s), 24 V ≐, Red Dome	200g	10	ea	
826.220.00	Permanent Light (B 15s), 24 V ≐, Green Dome	200g	10	ea	
826.320.00	Permanent Light (B 15s), 24 V ≐, Yellow Dome	200g	10	ea	
826.420.00	Permanent Light (B 15s), 24 V ≐, Clear Dome	200g	10	ea	
826.520.00	Permanent Light (B 15s), 24 V ≐, Blue Dome	200g	10	ea	
Connection:	Screw free clamp mechanism up to 1.5 mm ² ; Cable diameter 7 - 11 mm; Contact protection according to VDE				
Operating voltage:	max. 250 V for B 15d; max. 50 V for B 15s				
Bulb:	max. 15 W (not included - please order separately)				
Duty cycle:	100 % max. 15 W; 50 % max. 25 W				
Socket:	B 15d or B 15s				

827 – Series Blinking Light

827.100.75	Blinking Light (B 15d), 24 V ≐, Red Dome	220g	10	ea	
827.200.75	Blinking Light (B 15d), 24 V ≐, Green Dome	220g	10	ea	
827.300.75	Blinking Light (B 15d), 24 V ≐, Yellow Dome	220g	10	ea	
827.100.77	Blinking Light (B 15d), 115 V ~, Red Dome	220g	10	ea	
827.200.77	Blinking Light (B 15d), 115 V ~, Green Dome	220g	10	ea	
827.300.77	Blinking Light (B 15d), 115 V ~, Yellow Dome	220g	10	ea	
827.100.78	Blinking Light (B 15d), 230 V ~, Red Dome	220g	10	ea	
827.200.78	Blinking Light (B 15d), 230 V ~, Green Dome	220g	10	ea	
827.300.78	Blinking Light (B 15d), 230 V ~, Yellow Dome	220g	10	ea	

Connection: Screwable connection with wire protection 0.5 mm² - 2.5 mm²; Cable diameter 7 - 11 mm; Contact protection according to VDE
Operating voltage: 24 V ≐, 115 V ~, 230 V ~
Bulb: max. 25 W (not included - please order separately)
Blink frequency: 1.5 Hz
Starting current: at 24 V ≐ 3 A; at 115 V ~ 600 mA; at 230 V ~ 350 mA
Socket: B 15d

828 – Series Flashing Light

828.100.54	Flashing Light, 12 V =, Red Dome	220g	10	ea	
828.300.54	Flashing Light, 12 V =, Yellow Dome	220g	10	ea	
828.100.55	Flashing Light, 24 V =, Red Dome	220g	10	ea	
828.200.55	Flashing Light, 24 V =, Green Dome	220g	10	ea	
828.300.55	Flashing Light, 24 V =, Yellow Dome	220g	10	ea	
828.100.67	Flashing Light, 115 V ~, Red Dome	220g	10	ea	
828.200.67	Flashing Light, 115 V ~, Green Dome	220g	10	ea	
828.300.67	Flashing Light, 115 V ~, Yellow Dome	220g	10	ea	
828.100.68	Flashing Light, 230 V ~, Red Dome	220g	10	ea	
828.200.68	Flashing Light, 230 V ~, Green Dome	220g	10	ea	
828.300.68	Flashing Light, 230 V ~, Yellow Dome	220g	10	ea	

Connection: Screwable connection with wire protection 0.5 mm² - 2.5 mm²; Cable diameter 7 - 11 mm
Flash frequency: about 1 Hz
Flash energy: 5 Ws
Life duration: 4 x 10⁶ flashes
Operating voltage: 12 V = 24 V = 115 V ~ 230 V ~
Current consumption: 500 mA 300 mA 65 mA 150 mA

12 V: Safety contact is triggered by removal of dome

Catalog No. / Katalog-Nr. Description / Beschreibung

Weight/ea VPE/Pack U/M EDP-No.

826/827/828 – Series Accessories



Bracket (accessory)

- 975.826.05 Plastic bracket for wall mounting
- 975.826.03 Wire guard, galvanized, for base mounting
- 975.845.10 Tube Diameter 25 mm, all anodized aluminum, 100 mm long
- 975.840.90 Base for tube, plastic (must be ordered twice)

Bulb BA 15d for Permanent light 826-series,
Total length max. 45 mm

- 955.826.35 24 V, 15 Watts
- 955.826.38 230 V, 15 Watts



Tube with Base (accessory)

Bulb BA 15s for Permanent light 826-series,
Total length max. 48 mm

- 955.021.35 24 V, 21 Watts

Bulb BA 15d for Blinking light 827-series,
Total length max. 55 mm

- 955.827.35 24 V, 25 Watts
- 955.827.37 115 V, 25 Watts
- 955.827.38 230 V, 25 Watts

